

Valve Specification Sheet



MANUFACTURER : **SUFA (SEVERN)**

VALVE TYPE	Gate Valve,
CLASS RATING	ANSI 800
BODY CONSTRUCTION	Two piece, Bolted Bonnet, OS & Y, Rising Stem ASME B16.11, BS EN 12266 Rate B,
BORE	Regular Bore
VALVE OPERATOR	Hand Wheel Operated
END CONNECTIONS	Threaded ends NPTF.
BODY MATERIAL	(Forged) ASTM A276 F316
TRIM MATERIAL	Wedge: ASTM A276 F316 Stem: ASTM A276 F316
SEAT MATERIAL	ASTM A276 A276 F316 + HFS
SEAL MATERIAL	Stem Packing: Graphite Bonnet: Spiral wound gasket 316L/Graphite
BOLTING MATERIAL	Bonnet: A193 B8M
OTHER DETAILS	

1. Firesafe – inherently by design
2. Materials of Construction According to NACE MR-01-75
3. Certification According to BS/EN 10204 3.1.B.
4. Pressure Tested According to API.598
5. Face to Face According to ASME B16.34, ASME B16.5
6. Design According to API 602
7. Manufactured under API 6D Monogram
8. Manufactured under an ISO 9001 Certified Quality Assurance System.
9. CE/PED Compliant (1.1/4” and above) SEP all others.

**Where attached, please refer to drawing for design purposes only. Materials identified on this VDS supersede those of the drawing unless otherwise stated.*

REVISION	0	1	2	3	4	5	6
BY	KRF						
APP'D	BW						
DATE	13/09/13						