

Valve Specification Sheet



MANUFACTURER : **Starline (Italy)**

VALVE TYPE	Floating Ball Valve, Fig: 166NGG 'Megastar' 1/2" – 2"						
CLASS RATING	ANSI 1500						
BODY CONSTRUCTION	Three piece split bolted body. BS5351, ASME B16.34						
BORE	Full Bore						
VALVE OPERATOR	Lever Operated						
END CONNECTIONS	Flanged RTJ						
BODY MATERIAL	316 st/st						
TRIM MATERIAL	316 st/st						
SEAT MATERIAL	Devlon V						
SEAL MATERIAL	Viton / Graphite / RPTFE						
BOLTING MATERIAL	A193 B8						
OTHER DETAILS	<ol style="list-style-type: none"> 1. Firesafe Certified According to API 607/API 6FA/ISO 10497 2. Materials of Construction According to NACE MR-01-75 3. Certification According to BS/EN 10204 3.1.B. 4. Pressure Tested According to API.598 5. Face to Face According to ASME B16.34, ASME B16.5 6. Design According to API 6D and ANSI B16.34 7. Manufactured under API 6D Monogram 8. Manufactured under an ISO 9001 Certified Quality Assurance System. 9. CE/PED Compliant (1.1/4" and above) SEP all others. 10. Anti-static & Anti-blow out. <p><i>*Where attached, please refer to drawing for design purposes only. Materials identified on this VDS supersede those of the drawing unless otherwise stated.</i></p>						
REVISION	0	1	2	3	4	5	6
BY	KRF						
APP'D	BW						
DATE	17/09/13						